



SRW 360 comfortplus | eco 360 comfortplus

Fixed 3:1 or 2:1 pitch, electrical desktop punching and RENZ RING WIRE® binding machines for all types of book and calendar production. Designed to produce low to medium volumes of documents of all sizes quickly and easily.



Illustrated: SRW 360 comfort plus

Customer benefits:

- Binds up to 135 / 340 sheets(1)
- Closure control guarantees easy ring wire closure for perfect presentations every time
- Gauge to alter margin for a stronger bind
- Special hardened punch pins for long lasting life
- Staggered punching pins for better punching
- QSA (Quick Size Adjustment) for high flexibility of different paper formats: A5, A4 and A3
- Adjustable side lay for perfect punching registration
- Easy to empty sliding waste tray
- Measures the document or ring wire size
- Parallel adjustment guarantees a perfect bind every time
- Heavy duty construction & compact design

Maximum:



360 mm



Punch up to⁽¹⁾
2.5 mm



Bind up to⁽¹⁾
34 mm

Output:



Max. punched sheets per hour⁽¹⁾ **16,000**



Max. bound products per hour **250**







Vertical punching makes it easy to punch accurately every time.



QSA (Quick Size Adjustment) technology means that punching pins can be cancelled and paper formats can be changed quickly and easily.



Depth gauge feature allows the operator to adjust the punched hole margin from 2 mm to 4,5 mm. This adds strength to the bound edge.



Binds up to 340 sheets(1). The closure control guarantees quick and exact wire closing.

SRW 360 comfortplus

PITCH

3 holes per inch 34 loops in A4 24 loops in A5



2 holes per inch 23 loops in A4 16 loops in A5

eco 360 comfortplus

■ ¶ @NE PITCH°

Technical data: SRW 360 comfortplus eco 360 comfortplus Punching capacity - sheets per hr: 16.000 16.000 Min. punching width: 10 mm 10 mm Max. punching width: 360 mm 360 mm Min. unpunched length: 50 mm 50 mm Max. unpunched length: 500 mm 500 mm 2.5 mm Max. punching thickness: 2.2 mm Punching operation: Electric Electric Punch pattern: Square 4 x 4 mm Oblong 5.5 x 3.5 mm 2:1 Selectable punch pins (QSA): Yes Yes Variable margin depth: Yes Yes Binding thickness: 1 - 13.5 mm 1 - 34 mm 5,5 - 16 mm 6,9 - 38 mm Binding element Ø: 3/16" - 5/8" 1/4" - 1 1/2" Min. binding width: 10 mm 10 mm Max. binding width: 360 mm 360 mm Binding operation: Manual Manual No. of books output per hr: 250 250 180 180 No. of calendars output per hr: Machine dimensions L x W x H: 430 x 560 x 180 mm 430 x 560 x 180 mm Machine weight: 26 kg 26 kg Machine packaging dimensions L x W x H: 620 x 480 x 345 mm 620 x 480 x 345 mm 28.5 kg Machine weight with packaging: 28.5 kg 230/250V / 50Hz / 180W 230/250V / 50Hz / 180W Power requirement: 115/200V / 60Hz / 180W 115/200V / 60Hz / 180W



New motor

The new 180 watt comfortplus motor with a punching cycle of 1.2 seconds is almost twice as fast as the previous model.

Technical modifications may be made without notice.

1 mm = 10 sheets of paper, based on 80 gsm.

All performance outputs are based on 80 gsm paper and may vary depending on the product type, the working environment and the operator. For best punching results we recommend a paper thickness of 1.5 - 2.0 mm.