



SPB 360

Manual coil punching and electric inserting machine with integrated crimping and cutting device. Designed for low to medium volumes of plastic coil books production.




PREMIUM QUALITY WORLDWIDE
MADE IN GERMANY 





Customer benefits:

- Binds up to 160 sheets
- QSA (Quick Size Adjustment) for high flexibility of different paper formats: A5 and A4
- Adjustable side lay for perfect punching registration
- Special hardened punch pins for long lasting life
- Staggered punching pins for better punching
- Easy to empty sliding waste tray
- Unique electric roller for quick coil insertion
- Clever crimper and cutter for turning coil ends
- Measures the document or coil size
- Heavy duty construction & compact design

Maximum:

-  Width **360 mm**
-  Punch up to **2.0 mm**
-  Bind up to **16 mm**


Output:

-  Max. punched sheets per hour **8,000**
-  Max. bound products per hour **50**





Vertical punching makes it quick and easy to punch correctly every time.



QSA (Quick Size Adjustment) technology means that punching pins can be cancelled and paper formats can be changed quickly and easily.



The simple to use rubber roller threads the coil through the document quickly and effectively.




The integrated coil cutting and crimping unit gives the perfect finish to your document every time and crimps the plastic coil at a 45° angle.



SC pliers

can be used to crimp larger diameter coils or metal spirals.



New modular motor

The new electric modular motor can upgrade a manual SPB 360 to an electric punch and manual binding system. The new 180 watt *comfortplus* motor with a punching cycle of 1.2 seconds is almost twice as fast as the previous model.

Technical data:	SPB 360	Modular motor
Punching capacity - sheets per hr:	8,000	-
Min. punching width:	10 mm	-
Max. punching width:	360 mm	-
Min. unpunched length:	50 mm	-
Max. unpunched length:	270 mm	-
Max. punching thickness:	2 mm	-
Punching Operation:	Manual	-
Punch pattern:	Oval 5.0 x 4.0 mm	-
Pitch:	6.2865 mm = 0.2475"	-
Selectable punch pins (QSA):	Yes	-
Variable margin depth:	No	-
Binding thickness:	1 - 16 mm	-
Binding element Ø:	6 - 20 mm	-
Min. binding width:	10 mm	-
Max. binding width:	360 mm	-
Binding operation:	Electric insert, manual crimp and cut	-
No. of books output per hr:	50	-
Machine dimensions L x W x H:	360 x 490 x 250 mm	160 x 420 x 160 mm
Machine weight:	19 kg	13 kg
Machine packaging dimensions L x W x H:	620 x 480 x 345 mm	620 x 480 x 345 mm
Machine weight with packaging:	23 kg	15 kg
Power requirement:	230/250V / 50Hz / 90W 115/200V / 60Hz / 90W	230/250V / 50Hz / 180W 115/200V / 60Hz / 180W

Technical modifications may be made without notice.

1 mm = 10 sheets of paper, based on 80 gsm.

All performance outputs are based on 80 gsm paper and may vary depending on the product type, the working environment and the operator. For best punching results we recommend a paper thickness of 1.5 - 2.0 mm.

For further information and videos please visit: